Markilux 1300 Retractable Awning





EMAIL: ENQUIRIES@SAMSONAWNINGS.CO.UK TELEPHONE: (01933) 448844 MON - FRI 8:30AM - 5:30PM



Aluminium coverboard Protects the cover from dirt and moisture.



Pitch adjustment gear Changes the pitch from 4° to 85° using a crank handle.



Valance

This decorative piece of fabric conceals and protects the folding arm technology when the awning is retracted.



Select a standard frame colour between traffic white, RAL 9016, and metallic aluminium, RAL 9006, or, as an extra option, a RAL colour of your choice.

www.samsonawnings.co.uk

MX_1300



The beauty of simplicity.

markilux 1300

It is robust, reliable and fulfils all the expectations of a good awning. With the optional pitch adjustment gear, you yourself can determine the angle at which your awning cover protects you and your loved ones from the sun. Also if desired: a shadeplus, the versatile cover attached to the front profile to protect you from the low-lying sun and prying eyes.

The beauty of simplicity! And simply perfect protection against the sun.



The markilux shadeplus Enjoy relaxing on your patio even when the sun is low in the sky.



Open awning max. 700 × 400 cm

Arm technology twin round steel-link chains

Options

shadeplus / drop valance, valance, pitch adjustment gear, aluminium coverboard, coupled awning

markilux designer awnings

	markilux MX-1	markilux MX-1 compact	markilux 6000	markilux 5010	markilux 970	markilux MX-3
Max. width × projection	700 × 437 cm	700 × 415 cm	700 × 400 cm	700 × 400 cm	600 × 300 cm	600 × 300 cm
					500 × 350 cm	500 × 350 cm
Operation	Radio-controlled motor*	Radio-controlled motor *	Manual operation	Manual operation	Manual operation	Manual operation
optional	 silentec motor 	silentec motor	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation
			hard-wired motor	hard-wired motor	hard-wired motor	hard-wired motor
			silentec motor	😌 silentec motor	radio-controlled motor*	radio-controlled motor*
			radio-controlled motor*	• radio-controlled motor*		
Arm technology	Bionic tendon	Bionic tendon	Bionic tendon	Twin round steel-link chains	Bionic tendon	Bionic tendon
optional				Bionic tendon		
Fixture type	Face fixture	Face fixture	Face/top/eaves	Face/top/eaves	Face/top/eaves	Face/top/eaves
optional			• wall sealing profile	• wall sealing profile	• niche	• wall sealing profile
Options**						
	LED Line / Spots	LED Line / Spots	LED Spots in the front profile	😌 end caps front profile	LED Line in the cassette	LED Line in the cassette
	in the front profile	in the front profile	end cap insert in stainless steel mesh	in polished chome	LED Spots below the cassette	LED Spots below the cassette
	LED ambient lighting	LED ambient lighting	😌 end cap trim in polished chrome	😌 shadeplus / drop valance	anodised front panels	coloured front panels
	LED Spots below the cassette	LED Spots below the cassette	shadeplus / drop valance	valance	shadeplus / drop valance	and end cap insert
	choose your own colour combination	choose your own colour combination	valance	coupled awning		
	shadeplus / drop valance	shadeplus / drop valance	coupled awning			
	• valance	 ♥ valance 				
	* Remote control, smart (app) or intellige	ent control possible	** Some options cannot be combined			

markilux

markilux 990	markilux 3300	markilux 1710	markilux 1600	markilux 930	markilux 1700	markilux 1300			
						Con la constante de la constan			
500 × 300 cm	700 × 400 cm	700 × 350 cm	710 × 400 cm	500 × 300 cm	700 × 400 cm	700 × 400 cm			
Manual operation	Manual operation	Manual operation	Manual operation	Manual operation	Manual operation	Manual operation			
servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation	servo-assisted manual operation			
hard-wired motor	hard-wired motor	hard-wired motor	hard-wired motor	hard-wired motor	hard-wired motor	hard-wired motor			
radio-controlled motor*	 silentec motor radio-controlled motor* 	radio-controlled motor*	radio-controlled motor*	radio-controlled motor*	radio-controlled motor*	• radio-controlled motor*			
Twin round steel-link chains	Bionic tendon	Bionic tendon	Twin round steel-link chains	Twin round steel-link chains	Bionic tendon	Twin round steel-link chains			
Bionic tendon			Bionic tendon						
Face/top/eaves	Face/top/eaves	Face/top/eaves	Face/top/eaves	Face/top	Face/top/eaves	Face/top/eaves			
• wall sealing profile	wall sealing profileniche	• wall sealing profile	• wall sealing profile			aluminium coverboard			
• end cap insert in polished chrome	• valance	end caps and end cap insert	LED Spots in the front profile	• valance	end caps and end cap insert	shadeplus / drop valance			
• valance	coupled awning	in polished chome	end caps in polished chrome		in polished chome	valance			
		valance	shadeplus / drop valance		valance	pitch adjustment gear			
		coupled awning	valance		coupled awning	coupled awning			
		stretch	coupled awning		😌 stretch				
			stretch						
	mat Wind protection and extra p	privacy Page 46	markilux 790 Side screen Page 48 Extension: max.450 cm, height: 90 – 250 cm						
	ax. 300 × 250 cm, can be extended	uctom alamant	Operation: manual operation; Fixture type: can be fitted to a wall or in a niche						
	o demarcation, fixed to footings, awning s	ystem etement	Options: • angled top edge and mobilfix						
Options: Options, slide, panoramic window Options: Options:									

01933 448844

www.samsonawnings.co.uk

markilux awning systems markilux pergola markilux pergola compact markilux planet markilux markant markilux syncra markilux construct Max. width × projection 600 × 450 cm 450 × 400 cm 600/610 × 300 cm 600 × 600 cm (2 fields) Up to 60 m² Almost unlimited 500 × 600 cm 500/510×350 cm 300 × 600 cm (1 field) depending on the awning model Textile weather protection Awning system Awning-cum-parasol Awning stand system Frame system pergola pergola tracfix cover guidance Free-standing, purist in design, modular and flexible tracfix cover guidance with one with two posts with lateral guide tracks with lateral guide tracks markilux designer awning on four posts with and one/two on slim posts on slim posts as desired integrated designer awning markilux designer awnings or pergolas as desired Operation Hard-wired motor Hard-wired motor Depending on the awning model Radio-controlled motor* Depending on the awning model Depending on the awning model silentec motor radio-controlled motor* optional radio-controlled motor* Arm technology Depending on the awning model Depending on the awning model Depending on the awning model Fixture type Face/top/eaves Face/top/eaves Free-standing Free-standing Free-standing Free-standing wall sealing profile wall sealing profile on concrete foundations on concrete foundations on concrete foundations on concrete foundations or attached to a wall or stabilisation boxes Options** Depending on the awning model Depending on the awning model Depending on the awning model LED Line / LED Spots LED Line / LED Spots flex (335° pivoting) LED Line / LED Spots 🖯 uno • vertical roller blinds \rm flex shadeplus / drop valance • shadeplus / drop valance (manual) shadeplus / drop valance • wall sealing profile wind protection and extra privacy wind protection and extra privacy wind protection and extra privacy base plate covers vertical roller blinds round or square posts panoramic window round or square posts round or square posts wind protection and extra privacy base plate covers • round or square posts adjustable posts adjustable posts panoramic window coupled awning base plate covers stabilisation boxes stabilisation boxes coupled awning * Remote control, smart (app) or intelligent control possible ** Some options cannot be combined





Nationwide delivery and installation service



6-8 MEADOW CLOSE ISE VALLEY INDUSTRIAL ESTATE FINEDON ROAD WELLINGBOROUGH NN8 4BH EMAIL: ENQUIRIES@SAMSONAWNINGS.CO.UK TELEPHONE: (01933) 448844 MON - FRI 8:30AM - 5:30PM

