



Semi-cassette awning

markilux 1600 stretch

The awning with excellent design features and well-thought-out-mechanics. Large projections at limited widths – the perfect solution for narrow reveals, balconies and patios.



product
design award


markilux.com

markilux
safe timeless beautiful

Product characteristics

Wind resistance class 2

Beaufort 5 → 7.5–10.4 m/s → 28–37 km/h → 17–23 mph



1 face fixture



1 face fixture, maximum pitch 25°



1 top fixture




2 folding arm suspended from the torque bar



3 connection of the lower folding arm to the front profile



4 drop valance ¹⁾



5 twin steel-link chains, corrosion protected



5 bionic tendon made of high-tech fibres for optimum power transfer-ence ¹⁾



6 wall sealing profile up to a pitch of 25° ¹⁾



1) optional configuration

Product characteristics

Description

- the folding-arm awning with exceptional, organic design characteristics and pivoting coverboard, ideally suited for shading large areas. The smart engineered arm technology allows shading of areas with more depth than width.

Special features

- awning with an extremely torsion-resistant, round torque bar
- the tiered arms make greater projections than widths possible
- during the closing procedure, the coverboard tilts automatically down the given pitch of the awning and together with the front profile encloses the roller tube completely (the awning is open underneath)
- option of a drop valance up to a projection of 350 cm – vertical protection against low-lying sun and inquisitive glances integrated into the front profile, can be operated manually
- coverboard with integrated brush so that debris does not get dragged into the awning as it closes

Dimensions

- cassette in the standard version: depth 275 mm, height 297 mm
- single unit: minimum width 122 cm at the smallest projection of 150 cm, maximum width 247 cm at the largest projection of 400 cm

Roller tube and lateral bearings

- round roller tube Ø 85 mm with keyway, galvanised steel – excellent stability, ensures near perfect cover performance even at the largest widths
- the roller tube support bracket is made of extruded aluminium, powder coated, visually masked by the coverboard end cap

Awning profiles

- extruded aluminium, in façade quality, powder coated
- oval, single-piece coverboard, pre-fitted, enclosing the awning from behind and above
- semi-circular front profile incorporated into the coverboard during closing
- round torque bar Ø 50 mm, galvanised both inside and out, powder coated

folding arms

- profiles in extruded aluminium, in façade quality, powder coated
- moving parts made of drop-forged aluminium - the arms are therefore extremely fracture resistant
- pivot bolts in stainless steel run in Teflon-coated bronze bushes - practically maintenance free, virtually silent and extremely hard wearing
- power transference via corrosion-protected twin steel-link chains at the elbow joint, optionally with innovative bionic tendon made of high tensile, high-tech fibres – low in friction, noiseless, insensitive to corrosion and UV resistant

Side caps

- the coverboard end caps are made of high-quality plastic, powder coated
- the front profile and torque bar end caps are made of high-quality plastic, powder coated or in polished chrome

Fixture brackets

- face fixture, top fixture, eaves fixture
- extruded aluminium, powder coated
- pitch range 5°–25°, infinitely adjustable
- spacer plates, stand-off brackets and other accessories are available

Frame and end cap colours

markilux frame colours without surcharge

traffic white RAL 9016




metallic aluminium RAL 9006




grey brown, similar to RAL 8019



off-white textured finish, 5233 ¹⁾



stone grey metallic, 5215 ¹⁾




anthracite metallic, 5204 ¹⁾



11


Havana brown textured finish, 5229 ¹⁾



off-white textured finish, 5233 ¹⁾
front profile and torque bar end cap
in polished chrome



stone grey-metallic 5215 ¹⁾
front profile and torque bar end cap
in polished chrome



anthracite metallic, 5204 ¹⁾
front profile and torque bar end cap
in polished chrome



Combination options – possible in any frame colour

Non-standard powder-coated finish

Bespoke frame colours at a surcharge – matt, metallic and pearl finishes as well as other colour ranges (DB, Tiger etc.) on request.
All frame colours are available at a surcharge with enhanced corrosion protection

1) textured finish

Colours may differ slightly from those depicted in both hue and finish.

Dimensions and configuration options

Single unit

		Overall awning width								Minimum width			
		160	185	210	235	260	310	360	410	Motor		Crank handle	
		122 160	161 185	186 210	211 235	236 260	261 310	311 360	361 410				
Order dimensions	H	150	3)	2)	—	—	—	—	—	135	122	139	126
	200	3)	—	2)	2)	—	—	—	—	160	147	164	151
	250	—	3)	—	—	2)	—	—	—	185	172	189	176
	300	—	—	3)	—	—	2)	—	—	210	197	214	201
	350	—	—	—	3)	—	—	2)	—	235	222	239	226
	400 ^{1) 4)}	—	—	—	—	3)	—	—	—	260	247	264	251

1) = drop valance not available

2) = inside dimensions on request

3) = observe the minimum widths!

4) = only available with motor drive (surcharge)

H = projection

 = 2 folding arms, 2 brackets = 2 standard arms = 2 bespoke arms (surcharge)

dimensions in cm

Operation

	standard	optional
crank handle	✓	—
spring-assisted crank handle	—	✓
Hard-wired motor	—	✓
silentec motor (optionally with an external io / RTS receiver)	—	—
radio-controlled motor io, 868 MHz	—	✓
radio-controlled motor RTS, 433 MHz	—	✓
radio-controlled motor RTS, 433 MHz with manual override	—	✓

Coupled Awning

not available

Awning cover	fabric range no.	standard	optional
sunvas	301.. / 309..–315..	✓	—
perla	370 ..	—	✓
sunsilk	324.. / 325.. / 328.. / 369..	✓	—
perla FR	374.. / 375..	—	✓
perfortex	331.. / 332..	—	—
transolair	338..	—	—
vuscreen Alu	317..	—	—
Soltis Perform 92	92-20..	—	—
glass fibre screen	272..	—	—
volant, height 15 cm		✓	—

Shadeplus / drop valance	standard	optional
height 150 cm or 210 cm ¹⁾		
maximum projection 350 cm		
crank handle	✓	—
Hard-wired motor	—	—
radio-controlled motor io, 868 MHz	—	—
radio-controlled motor RTS, 433 MHz	—	—
cover	sunvas / sunsilk / transolair / vuscreen Alu ²⁾	

1) depending on the fabric width (fabric width 120 cm) with horizontal seam

2) vuscreen Alu: max. height 100 cm

Only available in plain seamless fabrics (oversized, fabric width > 120 cm) or in plains with a horizontal joint (fabric width 120 cm).

markilux 1600 stretch

Semi-cassette awning

Optional accessories

manual drop valance
folding arm technology with bionic tendon
wall sealing profile (effective up to a maximum awning pitch of 25°); coverboard when fitted to the markilux panel, in one piece
infrared heater 2500 W
infrared heater 2500 W with integrated radio-controlled receiver 868 MHz io
LED spotline – light bar 110 × 70 mm with 5 W LED spotlights, width 180 cm / 3 spots or 300 cm / 5 spots
LED spotline io – light bar 110 × 70 mm with 5 W LED spotlights with integrated dimmable radio-controlled receiver, width 180 cm / 3 spots or 300 cm / 5 spots
automatic controls (light, wind, rain)


N.B! Important background information can be found in the chapter “Optional Accessories”.

Fixture options

wall bracket 100 mm	70867.
spreader plate A 430 × 160 × 12 mm	75326.
spreader plate B 300 × 400 × 12 mm	75325.
markilux panel 250 × 230 × 49 mm	76308.
markilux panel continuous	76380.
stand-off bracket wide 80–300 mm	77968.
top fixture bracket 90 mm	70868.
eaves fixture bracket 90 mm, 150 mm plate	71612.
eaves fixture bracket 90 mm, 270 mm plate	71659.
flat plate and angled bracket for eaves fixture, machine finish aluminium, 500 mm plate	716620
spreader plate 260 × 60 × 12 mm for eaves fixture bracket	75383.
eaves fixture bracket adjustable 7,5°–60°	71198.

Bracket fixture range

Awning with 2 folding arms



dimensions in cm

		Overall awning width							
		160	185	210	235	260	310	360	410
Order dimensions		122 160	161 185	186 210	211 235	236 260	261 310	311 360	361 410
BHT		No. of brackets No. of fixing points							
W	10	2 6							
BP		A 2 16 B 2 8							
DE	9	2 8							
PA		2 8							
DA	9	2 8							


dimensions in cm

The **pull-out forces** necessary for determining the correct fixing materials necessary to meet wind resistance class 2 (Beaufort 5) can be found in the password-protected dealer area of the markilux.com website under “Pull-out Forces”.

- BHT = bracket width
- BP = spreader plate A or B, to be positioned behind the folding arm
- DA = eaves fixture bracket
- DE = top fixture bracket
- EA = deep folding-arm (opposite of the drive side)
- M = *order dimension* = awning width
- MH = bracket centre
- PA = markilux panel, fixture profile, width 250 mm
- W = face fixture bracket

Face fixture


Fixtures, fittings and accessories



70867.

face fixture bracket

100 mm




758831

spacer plate

100 × 150 × 20 mm


N.B!
Stack to a max. height of
200 mm



758841

spacer plate


100 × 150 × 12 mm



71843.

cover plate
for spacer plate
and stand-off brackets
in the case of external
insulation


230 × 210 × 2 mm



76385. and 704241


Wall sealing profile
incl. brush seal
when installing with a
coverboard

available by the metre





76386. and 2 × 735611

1 side plate including
2 pan-head self-tapping
screws for wall sealing
profile

bolt reduction
assembly

pack 10 pcs

M 16 → M 12 | M 16 → M 10 | M 12 → M 10 | M 10 → M 10







76385. = wall sealing profile (standard width = awning width (**M**); up to a maximum awning pitch of 25°)

dimensions in mm

Face fixture with spreader plate A

Fixtures, fittings and accessories




76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 25°)

dimensions in mm


Face fixture with spreader plate B

Fixtures, fittings and accessories




face fixture bracket
100 mm

70867.




spreader plate B
face fixture
300 × 400 × 12 mm

75325.




Wall sealing profile
incl. brush seal
when installing with a
coverboard
available by the metre

76385. and 704241




1 side plate including
2 pan-head self-tapping
screws for wall sealing
profile

76386. and 2 × 735611





stand-off strip for
wall sealing profile
available by the metre

751971



bolt reduction
assembly
pack 10 pcs

M 16 → M 12 | M 16 → M 10 | M 12 → M 10 | M 10 → M 10






751971 = stand-off strip for wall sealing profile


76385. = wall sealing profile (standard width = awning width (M); up to a maximum awning pitch of 25°)

dimensions in mm

Face fixture with markilux panel 250 mm

Fixtures, fittings and accessories


 markilux panel 250 mm fixture profile with decorative profiles and end caps 250 × 230 × 49 mm 76308.	 face fixture bracket 100 mm 70867.	 face fixture bracket for central fixture, depending on size 45 mm 71813.
--	--	---



dimensions in mm

Face fixture with markilux panel continuous

Fixtures, fittings and accessories




markilux panel 250 mm
fixture profile

with decorative profiles
and end caps


continuous

76380.



face fixture bracket
100 mm

70867.




face fixture bracket

for central fixture,
depending on size


45 mm

71813.




Coverboard brackets

76390.



Coverboard incl. addi-
tional profile and rubber
sealing strip

72015., 72019., 75970.




End cheeks for the cover-
board, 282 × 87 × 2 mm

and

3 fillister head self-tap-
ping screws

76469. und 3 × 735611

As a **continuous fixture profile**, the markilux panel will always be supplied to order on the basis of a technical drawing prepared in the factory in accordance with the awning specification.



L = individual width, max. 7000 mm


X = fixing point separation, **by way of example**

SD = coverboard

dimensions in mm



Face fixture with stand-off bracket

Fixtures, fittings and accessories




face fixture bracket

100 mm




70867.stand-off bracket
for face fixture bracket
70867.**77968.**cover plate
for spacer plate
and stand-off brackets
in the case of external
insulation

230 × 210 × 2 mm

71843.bolt reduction
assembly

pack 10 pcs


M 16 → M 12 | M 16 → M 10 | M 12 → M 10 | M 10 → M 10



dimensions in mm


Top fixture

Fixtures, fittings and accessories



top fixture bracket
90 mm

70868.




spacer plate for
top fixture
 $90 \times 140 \times 20$ mm
N.B!
stack to a max. height of
200 mm

716311



spacer plate for
top fixture
 $90 \times 140 \times 12$ mm


716411



dimensions in mm


Eaves fixture

Fixtures, fittings and accessories




eaves fixture bracket
90 mm
complete set
height of flat
plate: 150 mm

70871.




top fixture bracket
90 mm

70868.




eaves fixture bracket
flat plate
150 mm

71612.



eaves fixture bracket
270 mm plate
please refer to "Eaves
fixture with spreader /
backing plate"


71659.




flat plate and angled
bracket for eaves fixture
machine finish

716620

with eaves fixture bracket flat plate 150 mm (71612.)




with eaves fixture bracket flat plate 270 mm (71659.)




dimensions in mm

Eaves fixture with additional plate


Fixtures, fittings and accessories

**70871.**


eaves fixture bracket
90 mm
complete set
height of flat
plate: 150 mm

**70868.**


top fixture bracket
90 mm

**71612.**

eaves fixture bracket
flat plate
150 mm

**71659.**


eaves fixture bracket
270 mm plate
please refer to "Eaves
fixture with spreader /
backing plate"

**75383.**


supplementary flat plate
eaves fixture
260 × 60 × 12 mm
please refer to "Eaves
fixture with spreader /
backing plate"

11

with eaves fixture bracket 150 mm (70871.)




with eaves fixture bracket 270 mm (71659.)



dimensions in mm


Eaves fixture with adjustable bracket

Fixtures, fittings and accessories




top fixture bracket
90 mm

70868.



adjustable
eaves fixture bracket


71198.




dimensions in mm

Awning with shadeplus

Face fixture




Top fixture




76385. = wall sealing profile (standard width = awning width (**M**); up to a maximum awning pitch of 25°)

dimensions in mm

Face fixture, manual operation




Motor cable exit point



dimensions in mm

Face fixture, radio-controlled motor with manual override

Gearbox eye positions



dimensions in mm